

# U.S. ARMY FOREIGN SCIENCE AND TECHNOLOGY CENTER

AD 698082



SUSPENSION FOR TRACKED VEHICLES

COUNTRY: USSR

## TECHNICAL TRANSLATION

This document has been approved  
for public release and sale;  
its distribution is unlimited.  
It may be released to the  
Clearinghouse, Department of  
Commerce, for sale to the  
general public.

Reproduced by the  
CLEARINGHOUSE  
to Federal Scientific & Technical  
Information Springfield Va. 22151

**TECHNICAL TRANSLATION**

**FSTC-HT-23-185-70**

**SUSPENSION FOR TRACKED VEHICLES**

by

V. V. Yemel'yanenko, et al.

SOVIET PATENT NO. 212073

Translated for FSTC by ACSI

This translation is an unedited rendition of the original foreign text. Statements or theories advocated or implied are those of the source and do not reflect the position or opinion of the US Army Foreign Science and Technology Center. This translation is published with a minimum of copy editing and graphics preparation in order to expedite the dissemination of information. Requests for additional copies of this document should be addressed to the Defense Documentation Center, Cameron Station, Alexandria, Virginia, ATTN: TSR-1.

Soviet Patent No. 212073, Class 63c

Inventors: V. V. Yemel'yanenko, R. V. Yefimova, N. A. Litvinov and  
E. R. Mel'man

Applied for by the Chel'yabinsk Tractor Plant

Tracked vehicle suspensions are known which have a transverse balance beam spring-mounted on flat elastic rubber elements. The beam is hinged at the middle to the chassis of the vehicle while the ends are supported by the track carriers.

In the proposed suspension, the design is simplified by mounting the balance beam on a pivot at the center. The ends of the pivot are rigidly fixed to the midsection of supports whose ends rest on the chassis of the vehicle through rubber elastic elements.

The proposed suspension is shown in Fig. 1. Fig. 2 shows section A-A and Fig. 3 shows section B-B.

In transverse beam 1 of the chassis of the tracked vehicle is balance beam 2 resting at the ends on track carriers 3 while the center is mounted to turn on bearing 4 of pivot 5. The pivot is rigidly fixed to the midsection of supports 6 by means of caps 7 and bolts 8. Motion of pivot 5 in the axial direction is prevented by split rings 9 which fit into grooves in the supports and in the pivot. The end sections of the supports have receptacles for installation of flat elastic rubber elements 10 located on opposite sides of the longitudinal plane of supports 6. The elastic elements closer to the chassis beam are located between the receptacles of the supports and the receptacles of plates 11 fastened to the chassis beam, while the elastic elements further from the chassis beam are located between the receptacles of the supports and the receptacles of caps 12 fastened by bolts 13 to the chassis beam.

Loads from the weight of the vehicle chassis, the weight of the motor and the weight of overhanging equipment mounted on the vehicle are transmitted to the chassis beam and covers 12 through elastic elements 10 to supports 6 and pivot 5, and through bearings 4 to balance beam 2 and the track carriers.

Under considerable loads equal to the full limit of travel of the elastic elements, part of the load is transmitted directly through caps 12 to supports 6, and then through pivot 5 and balance beam 2 to track carriers 3. In this event, caps 12 act as limiters for dynamic travel of the elastic element.

#### THE INVENTION

A tracked vehicle suspension containing a transverse balance beam spring-supported by means of flat rubber elastic elements. The beam is hinged at the middle to the chassis of the vehicle and the ends rest on the track carriers. The design is simplified by mounting the balance beam on the midsection of a pivot, the ends of the pivot being rigidly fastened to the midsections of support beams whose ends rest on the chassis through elastic rubber elements.

UNCLASSIFIED

Security Classification

## DOCUMENT CONTROL DATA - R &amp; D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Foreign Science and Technology Center US Army Materiel Command Department of the Army		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE  SUSPENSION FOR TRACKED VEHICLES			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Translation			
5. AUTHOR(S) (First name, middle initial, last name)  V. V. Yemel'yanenko, et al.			
6. REPORT DATE 19 November 69		7a. TOTAL NO. OF PAGES 2	7b. NO. OF REFS N/A
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)  FSTC-HT-23-185-70	
b. PROJECT NO.  c. 0423100 2301  d. Hardin		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)  ACSI Control Number J-7360	
10. DISTRIBUTION STATEMENT  This document has been approved for public release and sale; its distribution is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY US Army Foreign Science and Technology Center	
13. ABSTRACT  A tracked vehicle suspension containing a transverse balance beam spring-supported by means of flat rubber elastic elements. The beam is hinged at the middle to the chassis of the vehicle and the ends rest on the track carriers. The design is simplified by mounting the balance beam on the midsection of a pivot, the ends of the pivot being rigidly fastened to the midsections of support beams whose ends rest on the chassis through elastic rubber elements.			

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	Tracked vehicle suspension Transverse balance beam						

\*U.S. GOVERNMENT PRINTING OFFICE : 1969 391-034 (2445)